

## Technical Information / Tehničke informacije

Product description / Opis proizvoda	Multilayer Parquet Board / Višeslojna parketna daska
Commercial name / Komercijalni naziv	Sinteros Europarquet / Sinteros Europarket
Thickness / Debljina (mm)	13
Width / Širina (mm)	192
Length / Dužina (mm)	2272 / 1117
Wearlayer thickness / Debljina gornjeg sloja (mm)	~ 2,8
Weight / Težina (kg/m <sup>2</sup> )	~ 7,5
<p>Taber Abraser - Lacquer's wear resistance / Taber test habanja – Otpornost sloja laka*</p> <p>According / prema ENV 13696</p> <p>abrasion penetration (revs) / prodiranje abrazije (broj obrtaja) Classic Lacquer &gt; 2500</p>	
<p>Reduction of sound weighted index - index "footfall" to the room below / Indeks redukcije zvuka – index "koraka" u sobi ispod</p> <p>According to / Prema NF EN ISO 140-8 - NF EN ISO 717-2, <math>\Delta L_w</math> in dB</p> <p>with 2 mm Tarkofoam/fl ex II <math>\Delta L=17</math> dB</p>	
Formaldehyde emission / Emisija formaldehida EN 13986	E1
Fire Safety Class / Klasa vatrootpornosti EN 14342:2008, DIN 4102-1	Dfl-s1 (B2)
<p>Thermal insulation value / Sposobnost toplotne izolacije (W/mK)</p> <p>board only / samo daska 0,13 – 0,21</p>	
Installation / Ugradnja **	Floating or Glue down / "Plivajuća" ili lepljenjem
<p>Underfloor heating compatible / Pogodnost ugradnje u uslovima podnog grejanja ***</p> <p>Low temperature (max 27°C), waterborne system or selfregulating electrical system / Niska temperatura (max 27°C), toplovodni sistem ili samoregulirajući električni sistem grejanja</p>	

\* Method not applicable for brushed products due to the structured surface / Metod nije primenljiv za brušene proizvode zbog strukture gornjeg sloja

\*\* Contact your flooring supplier for further infomation / Kontaktirajte Vašeg isporučioaca poda za detaljnije informacije

\*\*\* Not suitable for the wood species beech and maple / Ne važi za drvene vrste bukva i javor